


L150 Tack Tank

LeeBoy



The 150 Tack Distributor ideally serves the paving contractor dedicated to smaller projects. With a conservative 150 gallon capacity tank, this solution still contains many of the features and functionality of the larger units. Inclusive of a powerful Honda engine, the user-friendly design can either be trailer or skid mounted. Multiple additional options including remote in-cab controls or overnight heating can further enhance the end user's experience.

Performance Features:

- 150 Gallon Capacity Tank
- 4.8 hp (3.6 kw) Gas Engine
- 6' Wand with On/Off Valve
- 40' Heavy-Duty Recoil Hose Reel
- 3,194 lbs Loaded Weight
- 1" Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted or Skid-Mounted Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



L150 Tack Distributor Specifications



Tank Size	150 gallons
Dimensions (Trailer Configuration)	- Length: 10' 6" - Width: 6' 6" - Height: 5' 9" - Shipping Weight: 1,519 lbs
Dimensions (Skid Configuration)	- Length: 7' 6" - Width: 4' 3" - Height: 4' 9"
Engine	Gas Engine— 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon
Tank Dimensions	- Length: 30.75" - Width: 54.125" - Height: 36.25"
Asphalt Pump	- Specially designed 7 gallons per minute pump
Heat System	- One 300,000 BTU propane burner - One start burner - 40 lbs propane fuel tank
Temperature Gauge	- 50 - 300° F (10 - 149° C) - Adjustable angle faceplate
Flush Tank	- 7 gallons tank with reverse suction valve
Hose and Reel	- .5" x 40' heavy-duty recoil hose reel
Wand	- 6' wand with cold handles - On/off valve - Removable spray tip
Manhole	- 20" diameter - 10" diameter fill hole - 3 psi pressure relief
Clean Out	- 4"

Sampling Valve	- 1"
Additional Standard Equipment	- Waste bucket mount (trailer only) - 1" rear tank return - 2" in-tank overflow
Optional Equipment	<p>Engines</p> <ul style="list-style-type: none"> - Gas engine- 4.8 hp (3.6 kW) electric start - Hatz diesel - 7.2 hp (5.4 kW) electric start - Gas engine 12 hp (9kw) Electric start - Fuel: 1.32 gallons <p>Heat Systems</p> <ul style="list-style-type: none"> - Diesel Burner One 300,000 BTU diesel burner (only available with electric start engines) 7 gallon fuel tank Auto ignition diesel burner with outfire - Overnight Heat 120 volt/1000 watt Immersion element <p>Spraybar with 12' pattern</p> <ul style="list-style-type: none"> - Spraybar controls: In-truck wireless remote controls (requires spray bar option) - Spraybar with cab wireless controls - Spraybar lift with cab wireless controls - Spraybar with cab wireless controls and lift with cab wireless controls <p>Insulated Tank</p> <ul style="list-style-type: none"> Surge brakes in lieu of electric brakes Frame mounted toolbox Wheel chocks Fire extinguisher: 5lbs 2-5/16" ball hitch



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com



LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-4006.4-EN