

TDC600 Tack Distributor

LeeBoy®



The TDC600 Tack Distributor provides a cost-efficient option for large projects and is perfect for the all-inclusive commercial paving contractor. This chassis mounted tank, along with its many standard features, such as long-ranged wireless remote controls, allows you to complete many of your daily tasks with efficiency and ease. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

Performance Features:

- 600 Gallon Capacity Tank
- 24.8 hp (18.5 kW) Kubota Engine
- 12' Fully Circulating Folding Spraybar
- 150 GPM Viking Pump
- Wireless In-Cab Controls
- Automatic Rate Control
- One 300,000 BTU Diesel Burner
- Adjustable Material Temperature Set Point
- Optional Accessories Available



TDC600 Tack Distributor Specifications



Tank Size	- 600 gallons		- Bar section on/off for left wing, left center, right wing
Dimensions	- Dimensions are dependent upon type of truck purchased and options selected		- Mode selector: off, spray/bar circulate, tank circulate/hand spray, reverse suction, cleanout, calibration
Engine	- Kubota - 24.8 hp (18.5 kW)		- E-stop
Capacities	- Fuel: 16 gallon		- Two batteries with charger
Tank Dimensions	- Length: 64" - Width: 70" - Height: 42"	Manhole	- 20" diameter - 10" diameter fill hole - 3 psi pressure relief
Asphalt Pump	- 150 gallons per minute Viking asphalt pump	Clean Out	- 4"
Heat System	- One 300,000 BTU diesel burner - Five pass flue system - Galvanized exhaust stack	Sampling Valve	- 1"
Temperature Gauge	- 0 - 500° F - Adjustable angle faceplate	Additional Standard Equipment	- RAM mount and cradle for wireless in-cab controls - Waste bucket mount - 2" tank overflow - LED work light package: includes 2 work lights - Beacon light with mount
Flush Tank	- 7 gallons	Optional Equipment	- 14' spraybar - Electric spray bar lift/lower - Diesel spray down system (pulls from engine fuel tank): includes electric pump, retracting hose reel, and spray gun - Overnight Heat 120 volt/1500-watt Immersion element - Fender mounted toolbox - Wheel chocks - Fire extinguisher: 5lbs - Hand Spray Wand - 5' 2" wand with cold handles with on/off valve, and removeable spray tip - Hose and reel: .5" x 40' heavy-duty recoil hose and reel - Overnight battery charger / tender
Spraybar	- Brass, slotted nozzles and valves are non-clogging - Quick-disconnect allows operator to change spray widths in 4" increments - 12' full circulating bar - Two 4' center sections - Two 2' folding spraybar wings - Nozzles: spaced 4" centers on spraybar		
Wireless In-Cab Controls	- Color display with readouts for: engine rpm, engine fault status, system faults, engine hours, ground speed, application rate, spray width, material temperature, material temperature set point, mode selection, asphalt pump current speed, valve status, totals screen - Auto/Manual pump selector - Manual pump speed dial - Engine start/stop - Bar circulate/off/spray switch		

*Published Weights are approximate weight and will vary contingent on options.



ST Engineering LeeBoy, Inc. 500 Lincoln County Parkway Extension Lincolnton, NC 28092 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-2025.4-EN



Contract # 060122-VTL