



SERVICE & LUBE TRAILER

OIL | COOLANT | RECLAIM | ANTIFREEZE | DIESEL | DEF | GREASE

STANDARD FEATURES

TANK FEATURES

- Maximum of 10 Main Fluid Systems (see right)
- Configurations of 25, 55, and 115 Gallon Tanks
- 460 or 690 Gallon Combined Capacity
- 7 or 10 Gauge Steel • Color Coded Nozzle Couplers for Oil and Coolant
- Tank Vents
- Spinsecure™ Caps
- Tank Level Gauges

TRAILER FEATURES

- 7.5" x 1/4" Formed Frame
- Dexter® Torsion Axles and EZ Lube Hubs
- Electric Brakes with Breakaway Safety System
- 16" 10-Ply Tires 235/80R16 with Steel Wheels
- Replaceable Fenders and Rock Guard
- 7,000 lb. Enclosed Jack and Safety Tow Chains
- Adjustable Height 2 5/16" Ball Hitch
- Reflective Tape and LED Lights
- Wiring Wrapped in Protective Braid
- Dual Coat Gray Polyurethane Paint
- Lockable Hatch-Style, Weather-Sealed Doors
- Automatic Interior LED Lighting
- 12V Deep Cycle Marine Battery
- Fire Extinguisher

OPTIONS

Items with + can be added any time to expand the functionality of the trailer as your operation grows.

- WorkSight Light Tower +
- Electric/Hydraulic Jack +
- 14-Ply Tires, ST235/85R16, Load Range G
- Spare Tire Kit with 10 or 14-Ply Tires +
- Aluminum Wheels
- Custom Paint Color
- Solar Battery Maintainer +
- Spill Containment Kit +
- Static Discharge Reel +
- Electric Gauges on Operator Panel
- Five Drawer Tool Chest (2 max) +
- Extra Used Filter Drain Pan for 4 Filters +
- 30 Gallon Poly Oil Tank w/ 3 GPM Pump (2 max) +
- Can and Towel Holder +
- Stationary Side Steps

MAIN FLUID SYSTEMS

OIL SYSTEMS

- 50' Retracting Reel, 1/2" Hose
- 5:1 Samson® PM4 Oil Pump, 2.1 GPM+
- Mechanical Preset Nozzles (Quarts)
- <4 Micron Tank Vents & Post Pump Filter Option

USED OIL RECLAIM SYSTEM

- 50' Retracting Reel, 1" Hose
- 4 Way Valve to Empty/Fill with Single Pump
- Samson® DF200 Diaphragm Pump
- Used Filter Drain Pan for 2 Filters
- Maximum of 2 Tanks Connected

TOP OFF DIESEL SYSTEM

- 50' Retracting Reel, 1/2" Hose
- 1:1 Samson® PM2 Pump
- Mechanical Preset Nozzle (Quarts)



ADDITIONAL FLUIDS

DEF SYSTEM

- 100 Gallon Poly DEF Tank
- Closed 2-in-1 Pumping System with 12V Pump
- 35' or 50' Retracting Reel
- Digital Meter and 120V Heater Available

GREASE SYSTEM

- 35 lb. or 120 lb. Systems Available
- 75' Retracting Reel, 1/4" Hose
- 55:1 Samson® PM4 Pump

*Flow rates calculated with 15W40 at 50°F & 100 psi air.

COOLANT SYSTEM

- 50' Retracting Reel, 1/2" Hose
- 1:1 Samson® PM2 Pump
- Stainless Steel Tank
- Mechanical Preset Nozzles (Quarts)

USED COOLANT RECLAIM SYSTEM

- 50' Retracting Reel, 3/4" Hose
- 1:1 Samson® PM2 Pump
- 4 Way Valve to Empty/Fill with Single Pump
- Maximum of 2 Tanks Connected

DIESEL SYSTEM

- Industrial Grade 12V or Gas Powered Pump
- 35' or 50' Retracting Hose Reel
- Extruded Aluminum Pump Manifold
- 10 Micron Filter or Two-Stage Filter Option (10+4)
- 12V Deep Cycle Battery and 12' Power Cables
- Auto-Trip Nozzle
- Analog and Digital Fuel Meter Options
- Electric Manifold Option

PNEUMATIC SYSTEMS



A Power Sliding Compressor Mount is installed in the SS Box. The air reels can be mounted either in the SS Box or in the Rear Utility Box.

- Comp+Gen with 50' Air/Electric Combo Reel
- Air Compressor with 50' Air Reel
- Air Line Plumbed through Hitch for External Air Supply



SPECIFICATIONS

Shown with optional aluminum wheels

		
Model	SLT460	SLT690
Tanks	460 gallon combined capacity 7 & 10 gauge	690 gallon combined capacity 7 & 10 gauge
Torsion Axles Hubs	dual 6,000 lbs. 8 bolt hubs	dual 7,000 lbs. 8 bolt hubs
L W H	19' 4" 7' 6"	21' 4" 7' 6"
Empty Weight* GVWR	6,400 lbs. 12,000 lbs.	7,200 lbs. 14,000 lbs.