



SERVICE & LUBE UPFIT

MEDIUM-DUTY PREVENTATIVE MAINTENANCE TRUCK



FEATURED MODEL: SLU690, CHEVY 5500

STANDARD FEATURES

- Maximum of 10 Main Fluid Systems (see right)
- Configurations of 25, 55 and 115 Gallon Tanks
- Up to 920 Gallon Combined Capacity
- 10 Gauge Mild or Stainless Steel Tanks
- Color Coded Nozzle Couplers for Oil and Coolant
- Spinsecure™ Caps, Vents, and Tank Level Gauges
- Reflective Tape and LED Lights
- Wiring Wrapped in Protective Braid
- Dual Coat Polyurethane Paint
- Lockable Hatch-Style, Weather-Sealed Doors
- Automatic Interior LED Lighting
- Fire Extinguisher
- VMAC Underhood Air Compressor + 50' Reel

*Flow rates calculated with 15W40 at 50°F & 100psi air.

MAIN FLUID SYSTEMS

OIL SYSTEM

- 50' Retracting Reel, ½" Hose
- 5:1 Samson® PM4 Oil Pump, 2.1 GPM*
- Mechanical Preset Nozzles (Quarts)
- <4 Micron Tank Vents & Post Pump Filter Option

USED OIL RECLAIM SYSTEM

- 50' Retracting Reel, 1" Hose
- 4 Way Valve to Empty/Fill with Single Pump
- Samson® DF200 Diaphragm Pump
- Used Filter Drain Pan for 2 Filters
- Maximum of 2 Tanks Connected

DIESEL SYSTEM

- 50' Retracting 1" Hose Reel
- Samson® DF200 Diaphragm Pump
- Auto-Trip Nozzle
- Digital Fuel Meter

TOP OFF DIESEL SYSTEM

- 50' Retracting Reel, ½" Hose
- 1:1 Samson® PM2 Pump
- Mechanical Preset Nozzle (Quarts)

COOLANT SYSTEM

- 50' Retracting Reel, ½" Hose
- 1:1 Samson® PM2 Pump
- Stainless Steel Tank
- Mechanical Preset Nozzles (Quarts)

USED COOLANT RECLAIM SYSTEM

- 50' Retracting Reel, ¾" Hose
- Samson® DF200 Diaphragm Pump
- 4 Way Valve to Empty/Fill with Single Pump
- Maximum of 2 Tanks Connected

DEF DELIVERY SYSTEM

- DEF Pump
- Stainless Steel DEF Tank
- 50' x 3/4" Retracting Hose Reel
- Auto-Trip Nozzle
- MicroMatic® Coupler
- Stainless Steel Quick Couplers

GREASE SYSTEM

- 35 lb. or 120 lb. Systems Available
- 75' Retracting Reel, 1/4" Hose
- 55:1 Samson® PM3 Pump



OPTIONS

- LED Work Lights
- Custom Paint Color
- Spill Containment Kit
- Electric Gauges on Operator Panel
- Tool Chest
- Extra Used Filter Drain Pan for 4 Filters
- Underbody Storage Boxes (24" x 24" x 48")
- Hazard Light Kit

SPECIFICATIONS

Model	Ford F-F550/F-600, RAM 5500, Chevy 5500/6500, or International CV515
GVWR	19,500 lbs. or Greater
Wheelbase	193"
Cab to Axle	108"
Drive Train	4x4 or 4x2
Body	Regular Cab